



ANEXO CONVOCATORIA 2209/2014

RENGLONES

Reglón	Especificación técnica
1	<p><u>UniFi AP PRO</u></p> <p>Dimensions: 200 x 200 x 36.5 mm (7.87 x 7.87 x 1.44 in)</p> <p>Weight: 298 g (10.51 oz) without Mounting Kits 358 g (12.63 oz) with Mounting Kits</p> <p>Networking Interface: (2) 10/100/1000 Ethernet Ports</p> <p>Buttons: Reset</p> <p>Antennas</p> <p>2.4 GHz Integrated 5 dBi Omni (Supports 3x3 MIMO with Spatial Diversity)</p> <p>5 GHz Integrated 4 dBi Omni (Supports 2x2 MIMO with Spatial Diversity)</p> <p>Wi-Fi Standards: 802.11 a/b/g/n</p> <p>Power Method: Passive Power over Ethernet (48V), 802.3af Supported</p> <p>Power Supply: 48V, 0.5A PoE Gigabit Adapter (Included)</p> <p>Maximum Power Consumption: 12 W</p> <p>Maximum TX Power:</p> <p>2.4 GHz 30 dBm</p> <p>5GHz 22 dBm</p> <p>BSSID: Up to Four Per Radio</p>



Power Save:	Supported
Wireless Security:	WEP, WPA-PSK, WPA-TKIP, WPA2 AES, 802.11i
Certifications:	CE, FCC, IC
Mounting:	Wall/Ceiling (Kits Included)
Operating Temperature:	-10 to 70° C (14 to 158° F)
Operating Humidity:	5 - 80% Non-Condensing

Advanced Traffic Management

VLAN:	802.1Q
Advanced QoS:	Per-User Rate Limiting
Guest traffic isolation:	Supported
WMM:	Voice, Video, Best Effort, and Background
Concurrent Clients:	200+

Supported Data Rates (Mbps)

Standard:	Data Rates
802.11a:	6, 9, 12, 18, 24, 36, 48, 54 Mbps
802.11n:	6.5 Mbps to 450 Mbps (MCS0 - MCS23, HT 20/40)*
802.11b:	1, 2, 5.5, 11 Mbps
802.11g:	6, 9, 12, 18, 24, 36, 48, 54 Mbps



ANA MARÍA MÉNDEZ
Directora de Compras