



## ANEXO CONVOCATORIA

2239/2022

### RENGLONES

Renglón	Especificación Técnica
1	<p>CARACTERÍSTICAS:</p> <ul style="list-style-type: none"><li>*IR resolution: 320 × 240pixels</li><li>*Thermal sensitivity/NETD: &lt;0.05°C (0.11°F) / &lt;60 mK</li><li>*Image adjustment: Automatic/Manual</li><li>*Field of view (FOV): 45° × 34°</li><li>*Minimum focus distance: 0.5 m (1.6 ft.)</li><li>*Image frequency: 9 Hz</li><li>*Focus: Focus free</li><li>*Wi-Fi: Peer-to-peer or network</li><li>*Detector type: Uncooled microbolometer</li><li>*Display. 3.0 in. 320 × 240 color LCD</li><li>*Image modes: Thermal MSX®, thermal, picture-in-picture, thermal blending, digital camera</li><li>*Multi Spectral Dynamic Imaging (MSX): IR image enhanced with visible camera detail</li><li>*Picture in Picture: IR area on visual image</li><li>*Color palettes: Black &amp; white, iron, and rainbow</li><li>*Digital camera resolution/FOV: 640 × 480/55° × 43°</li><li>*Object temperature range: -20°C to +550°C</li><li>*Accuracy: ±2°C (±3.6°F) or ±2% of reading, for ambient temperature 10°C to 35°C (+50°F to 95°F) and object temperature above +0°C (+32°F)</li><li>*Spotmeter; area: Center spot; box with min./max.</li><li>*Emissivity table/correction: Emissivity table of predefined materials/variable from 0.1 to 1.0</li><li>*File formats: Standard JPEG, 14-bit measurement data included</li><li>*Interfaces: USB Micro: Data transfer to and from PC and Mac device</li><li>*Battery type &amp; operating time: Rechargeable 3.6 V Li ion battery; approx. 4 hours typical use</li><li>*Encapsulation/drop: IP 54 (IEC 60529)/2m (6.6 ft.)</li><li>*Camera weight,incl. battery: 0.575 kg (1.27 lb.)</li></ul> <p>*INCLUIR SOFTWARE FLIR TOOLS, CERTIFICADO DE CALIBRACIÓN, MALETA RIGIDA, CARGADOR, 2 BATERIAS, CARGADOR EXTERNO, MANUAL, CABLE MICROUSB-USB Y CONEXION WIFI. *GARANTÍA DE 2 AÑOS DE LA CÁMARA, 5 DE LAS BATERIAS Y 10 AÑOS DEL DETECTOR.-</p>

---

Cra. JULIETA ROGLICH  
Directora de Compras